

VULCAN DD 40

PRODUCT DESCRIPTION

VULCAN DD 40 is a monograde diesel Two-Stroke engine oil developed for the lubrication of Detroit Diesel engine series 53, 71, 92 and 149 requiring API CF-2 quality engine oil.

APPLICATIONS

- Heavy goods vehicles in general transport
- Construction and heavy earthmoving equipment
- Marine engines used off-shore service support vessels
- Agriculture tractors
- Certain transmissions for earthmoving equipment

PERFORMANCE STANDARDS

VULCAN DD 40 meets and exceeds the International specifications:

API CF-2,

API CD II

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

VULCAN DD 40 provides:

- ◆ An economical product with good all round performance
- ◆ Suitability for use in light turbocharging
- ◆ Excellent resistance to oxidation
- ◆ Good engine cleanliness with special detergent/dispersant properties
- ◆ Good resistance to corrosion

Technical Data*	
SAE Grade	40
Density @ 15 ⁰ C	0.8845
Kinematic Viscosity mm ² /s @ 40 ⁰ C	156.1
Kinematic Viscosity mm ² /s @ 100 ⁰ C	15.48
Viscosity Index	100
Flash Point, COC, ⁰ C	248
Pour Point, ⁰ C	-15
BN No.ASTM D2896	6
Sulphated Ash %m	0.82
Product Code	200030

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.