

# ENOC PROTEC HD SF

## PRODUCT DESCRIPTION

**ENOC PROTEC HD SF** is a monograde engine oil developed for gasoline and naturally aspirated diesel engines. It is ideally suited for use in cars and light trucks where the customers needs can be met with a cost effective lubricant using standard oil change periods. **PROTEC HD** exceeds the API classification SF and CC

## APPLICATIONS

- ◆ Passenger cars and light commercial vehicles
- ◆ Agriculture tractors
- ◆ Pumps using small gasoline and diesels engines
- ◆ Portable generator sets

## PERFORMANCE STANDARDS

**PROTEC HD SF** meets and exceeds the following International specifications:

API SF/CC

CCMC G2, D1

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**PROTEC HD SF provides:**

- ◆ Good performance in gasoline and diesel engines
- ◆ Control of sludge and deposits
- ◆ Advanced detergent/dispersant properties
- ◆ Resistance to oil thickening

Technical Data*		
SAE Grade	40	50
Kinematic Viscosity		
mm <sup>2</sup> /s @ 40 <sup>o</sup> C	156.3	254
mm <sup>2</sup> /s @ 100 <sup>o</sup> C	15.26	21.5
Viscosity Index	97	100
Flash Point, COC, <sup>o</sup> C	248	260
Pour Point, <sup>o</sup> C	-15	-15
Product Code	210007	210015

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.