

ENOC RUST RESIST FLUID

PRODUCT DESCRIPTION

ENOC RUST RESIST FLUID is a dewatering and rust preventive fluid. This product coats the surface with a fatty soft film to provide a long term protection during outdoor sheltered storage.

APPLICATIONS

- ◆ Rust preventive applications for use in the metal industry or after a surface treatment
- ◆ Good water – repellent capability
- ◆ Protection guaranteed during 18 months in case of indoor storage and 12 months in case of outdoor storage under rain –shelter
- ◆ Can be applied by dipping, spraying, brushing. The film may be eliminated by alkaline detergent or solvent

PERFORMANCE STANDARDS

- ISO 6743/8 (1987): REE category
- MIL-VV-L-800C

Typical Characteristics	
Appearance	Liquid
Colour	Dark red
Density @ 15 °C g/mm ³	0.850
Viscosity, un-diluted mm ² /s @ 40 °C	6
Flash point C	38
Pour point C	-20
Water displacement power	yes

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.