

ENOC PROTEC HD

PRODUCT DESCRIPTION

ENOC PROTEC HD is a monograde engine oil suitable for gasoline and naturally aspirated diesel engines. It has been developed for use in older cars and light trucks and some model heavy truck engines where the needs of customers can be met with a very cost effective lubricant using standard oil change periods.

APPLICATIONS

- Passenger cars and light commercial vehicles
- Older model heavy duty trucks
- Agriculture tractors
- Small gasoline and diesels engines
- Portable generator sets

PERFORMANCE STANDARDS

PROTEC HD meets and exceeds the following International specifications

API SE/CC CCMC G1

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

PROTEC HD Provides:

- Good performance in gasoline and diesel engines
- Control of sludge and deposits
- Effective detergent/dispersant properties
- Resistance to oil thickening

Technical Data*		
SAE Grade	40	50
Kinematic Viscosity		
$mm^2/s @ 40^0C$	154	234
mm ² /s @100 ⁰ C	15.5	20
Viscosity Index	95	95
Flash Point, COC, ⁰ C	250	270
Pour Point, ⁰ C	-6	-6

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.