



ENOC TRACTOR STO

PRODUCT DESCRIPTION

TRACTOR STO oils are high quality all-purpose multigrade tractor oils for the agriculture market known as Super Tractor Oil Universal oils. They are recommended as an all-year round oil meeting many tractor manufactures specifications and providing excellent performance in all tractor applications; hydraulics, transmissions and engine. They can be used in agriculture tractors and other agricultural equipment with the benefit of one oil for all these lubrication applications.

APPLICATIONS

- ◆ Agriculture tractors Ford, Massey Ferguson and others recommending STOU applications
- ◆ Mixed fleet agriculture equipment
- ◆ Tractor universal transmission meeting John Deere J20 A, MF M 1135 specifications
- ◆ Transmissions requiring API GL-4 and Allison C-4 fluid
- ◆ Hydraulic systems with performance meeting ISO HV 68/100

PERFORMANCE STANDARDS

TRACTOR STO meets and exceeds the following OEM and International specifications:

| | | | |
|-----------------|----------|------------------|-----------------|
| FORD | M2C 159B | Allison | C-4 |
| API | GL-4 | API | CD, MIL-L-2104C |
| John Deere | J20 A | Hydraulic system | ISO HV 68/100 |
| Massey Ferguson | M 1135 | | |

Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.

BENEFITS

TRACTOR STO provides:

- ◆ Rationalisation requiring only one oil for all farm equipment lubrication
- ◆ Saves on inventory cost, ordering and administration
- ◆ Protects all farm equipment against potential damage through the wrong oil being used
- ◆ Provide long equipment life by ensuring the right oil is used every time
- ◆ Robust additive technology ensures smooth and quiet transmission in wet brake operation
- ◆ Low maintenance costs compared with using individual oils

| Technical Data* | | | |
|----------------------------|--------|--------|--------|
| SAE grade | 15W-30 | 15W-40 | 20W-40 |
| Density @ 15 °C | 0.880 | 0.8789 | 0.8828 |
| Viscosity | | | |
| mm ² /s @ 100°C | 11.29 | 14.49 | 15.6 |
| mm ² /s @40°C | 85.02 | 108 | 140 |
| Viscosity Index | 122 | 138 | 115 |
| Flash point COC °C | 218 | 220 | 228 |
| Pour Point, °C | -30 | -30 | -24 |
| Product code | 262002 | 262004 | 262003 |

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.