



# ENOC VULCAN 770 SLD

## PRODUCT DESCRIPTION

**ENOC VULCAN 770 SLD 10W-40** is a fully synthetic Extra or Super High Performance long drain synthetic diesel engine oil developed for modern low emission European trucks meeting the EURO IV emission standards. This lubricant has been developed to exceed Mercedes Benz 228.5 and Volvo VDS- 3 and other long oil drain specifications. **VULCAN 770 SLD** offers the ultimate performance for fleet operators wanting long engine life in modern long haul low emission diesel trucks operating on extended long drain periods.

## APPLICATIONS

- ◆ European engines used in long drain, high mileage applications
- ◆ Modern low emission high performance automotive diesel engines – Euro IV
- ◆ All vehicle makes used in mixed vehicle transport with extended oil drain capabilities
- ◆ Heavy duty Mobile Plant vehicles
- ◆ Diesel generator sets

## PERFORMANCE STANDARDS

**VULCAN 770 SLD** meets and exceeds the following OEM and International Specifications:

Mercedes Benz	228.5	Renault	VI RLD- 2
Volvo	VDS-3	IVECO	ACEA E4
MAN	M 3277	ACEA	E7- O4
API	CI- 4	MTU category	3
MACK	EO- N		

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**VULCAN 770 SLD provides:**

- ◆ Excellent engine cleanliness through advanced soot handling technology
- ◆ Mixed fleet capabilities
- ◆ Exceptional low engine wear
- ◆ Trouble free operation between long drain service intervals
- ◆ Reduced maintenance capabilities
- ◆ Easy starting due to its high fluidity

Technical Data*	
SAE Grade	<b>10W- 40</b>
Density at 15 <sup>0</sup> C	0.8560
Kinematic Viscosity mm <sup>2</sup> /s @ 40 <sup>0</sup> C	102.76
Kinematic Viscosity mm <sup>2</sup> /s @ 100 <sup>0</sup> C	15.31
Viscosity Index	160
Flash Point, COC, <sup>0</sup> C	234
Pour Point, <sup>0</sup> C	-36
BN No. ASTM D2896	12.74
Sulphated Ash % m	1.53
Product code	200031

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.