



# ENOC PROTEC MAX

## PRODUCT DESCRIPTION

**ENOC PROTEC MAX** offers a range of superior quality multigrade motor oils formulated to meet most American, European and Japanese car manufacturers' specifications. Its formulation is specifically designed for city operations where traffic conditions involve stop - start vehicle patterns as well as general long distance driving.

## APPLICATIONS

- ◆ All passenger Cars
- ◆ Gasoline four stroke engines used in many light duty applications
- ◆ Ideal for multi-trip mini vans

## PERFORMANCE STANDARDS

**PROTEC MAX** meets and exceeds the following International specifications:

API SF, CC  
CCMC G2 and D1

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**PROTEC MAX provides:**

- ◆ Prolonged engine life through excellent wear protection of engine components
- ◆ Superior oil consumption control through advanced detergent/dispersant technology
- ◆ Reduced engine deposits, varnish and lacquer
- ◆ Suitability for older engines

Technical Data*				
SAE Grade	10W-30	10W-40	15W-40	20W-50
Kinematic Viscosity				
mm <sup>2</sup> /s @ 40°C	68	96	110	155
mm <sup>2</sup> /s @ 100°C	11	14.5	14.3	17
Viscosity Index	152	155	135	115
Flash Point, COC, °C	216	215	222	230
Pour Point, °C	-33	-33	-27	-24
Product Code	210019	210014	210026	210002

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.